

STFMMINI

Suretime Mini Flush Mount 360 Degree PIR

Features & Benefits

- Flush mount PIR sensor suited for a wide array of indoor applications
- Manual override (Pulse) for extended light on times.
- Adjustable time ON setting
- Adjustable lux level
- Compact design



Technical Data

| | |
|---------------------------|---------------|
| Operating Voltage | 230V AC |
| Frequency | 50Hz |
| Installation Type | Flush Mount |
| Earth Class Rating | Class II |
| Operating Temperature | -20°C to 40°C |
| Ingress Protection Rating | IP44 |
| Setting Type | Dial |
| Max Mounting Height (Mtr) | 3 |
| Motion Detection (Mtr) | 6 |
| Detection Angle | 360° |
| Hole Cut-Out Size (mm) | 40 |

Data sheet

STFMMINI

Light / PIR Presence Detectors

| | |
|------------------------------|---|
| Standby Consumption | <1W |
| Number of Channels | 1 |
| Switch rating | 200W LED, 1000W Halogen, 200W Fluorescent/Low Energy Lighting |
| ON Time Adjustment | 3 Seconds to 18 Minutes. User Adjustable |
| Lux Level | 10 to 1000 |
| Detection Range (Mtr) | 6 |
| Permanent ON Facility | Yes (Pulse Override) |
| Dusk Till Dawn | No |
| Multiple Unit Support | Yes (Up to 5 In Parallel) |
| Cable Entry(s) | Back Entry |

General

| | |
|-------------------------------|---------------------|
| Weight (g) | 51 |
| Height (mm) | 73 |
| Width (mm) | 50 |
| Depth (mm) | 50 |
| Body Construction | Polycarbonate |
| Product Colour | White |
| Accessories (Included) | Cover Cover, Screws |
| EAN Number | 5012483014295 |
| Guarantee Period | 2 Years |

Line Diagrams

