# Data sheet STLB1000

#### Light / PIR Presence Detectors

### STLB1000

### **Suretime Outdoor PIR Black**

### **Features & Benefits**

- Manual override (Pulse) for extended light on times
- · Adjustable time ON setting
- Adjustable lux level



### **Technical Data**

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP55
Setting Type	Dial
Max Mounting Height (Mtr)	2.5
Motion Detection (Mtr)	8 to 12
Detection Angle	180°
Mounting Hole Centres (mm)	58



A **theben** Group Company

Subject to technical changes and misprints

additional information at: https://www.timeguard.com This data was generated on

17/05/2022

# Data sheet **STLB1000**

Standby Consumption	<1W
Number of Channels	1
Switch rating	200W LED, 1000W Halogen, 200W Fluorescent/Low Energy Lighting
ON Time Adjustment	3 Seconds to 18 Minutes. User Adjustable
Lux Level	10 to 1000
Detection Range (Mtr)	8 to 12
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Yes (Up to 5 In Parallel)
Cable Entry(s)	Back Entry, Bottom Entry

#### General

Weight (g)	119
Height (mm)	76
Width (mm)	76
Depth (mm)	87
Body Construction	Polycarbonate
Product Colour	Black
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483014301
Guarantee Period	2 Years



A **theben** Group Company

Subject to technical changes and misprints

additional information at: https://www.timeguard.com


This data was generated on

17/05/2022

### Data sheet STLB1000

### Light / PIR Presence Detectors

### Line Diagrams





Subject to technical changes and misprints

additional information at: https://www.timeguard.com

This data was generated on