

GLS BULB B22 1055LM 8W 2700K DIMMABLE 240 BEAM FROSTED INTEGRAL

ILGLSB22DC024



General

Warranty (Years)	2
Product Type	GLS

Physical Data

Globe Type	GLS
Bulb Base	B22
Base Term	Bayonet cap
Construction	Aluminium and Plastic heat-sink, Injection moulded diffuser

Light Data

Luminous Flux in Lumens (lm)	1055
Luminous efficacy (lm/W)	131
Instant on (Less than 1 second)	Yes
Correlated Colour Temperature (CCT) (K)	2700
Colour Temperature Name	Warm
Beam Angle (Range)	220+
Switching cycles	12500
Lifetime (hours)	15000
LED Type	Surface mounted device (SMD)
Colour Rendering Index (CRI)	80
Beam Angle	240
Lumens Range	850 to 1500

Electrical Data

Power Consumption (Range)	5 to 8 8 to 15
Input Current (A)	55

Wattage equivalent (W)	75
Power Factor	0.7
Power Consumption (w)	8
Voltage Range (v)	220-240

Environmental

New Energy Rating	E
IP Rating (Ingress Protection)	IP20 IP20
Previous Energy Rating	A+

Electrical Data, Environmental

EN	EN-62560
LVD Certified	Yes

Product Specification

Warranty (Years)	2
Housing Material	Plastic, Polycarbonate, Nickel plated brass

Key Features

Bullet 1	Warm Light
Bullet 2	1055 Lumens
Bullet 3	Dimmable

Environmental Specification

Minimum operating temperature (degrees Celcius)	-20
Maximum operating temperature (degrees Celcius)	40