




Product Description: PrincetonPRO™ 1500mm 30W Linear


The Princeton™ PRO surface mounted LED linear batten offers up to 50% energy savings in comparison to the traditional fluorescent alternative. The high quality polycarbonate diffuser ensures uniform light distribution, eliminating hot spots. Delivering 110lm/W, the batten matches the footprint of traditional fluorescents so is perfect for retrofitting. Fitted with push-fit terminal block for even faster installation.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-SF1530/40	30	4000	3300	110	110	White	Non Dimmable
EN-SF1530DA/40	30	4000	3300	110	110	White	DALI Dimmable
EN-SF1530EM/40	30	4000	3300	110	110	White	Emergency
EN-SF1530V/40	30	4000	3300	110	110	White	1-10V Dimmable

Line Drawing



Polar Curve



Colour



White

Product Features:

- Steel housing and high quality polycarbonate diffuser
- IK06 rated impact resistance
- Multiple BESA mounting points
- 5 Year Warranty
- Delivering 110lm/W
- Stand version fitted with push-fit terminals for fast installation

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.92	IP Rating	IP20
Lifetime L70 (hrs)	50000	IK Rating	IK06
Width (mm)	208	Length (mm)	1488
Weight (Kg)	0.132	Height (mm)	70
Product Type	Linears	Operating Temp. (Min) °C	-30°C
Operating Temp. (Max) °C	50°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.