

## Emergency Hanging Sign Surface Mounted 3W LED LIFEPO4


Surface mounted slim profile hanging exit sign, Ideal for all commercial, Leisure and Hospitality emergency lighting applications. Open areas, escape routes and exits

- 3 hour emergency maintained or non-maintained operation
- Polycarbonate and aluminium housing with interchangeable PVC legends
- Double sided acrylic hanging legend panel: Max. 700mm suspension
- Test function button and LED indicator
- Push-fit terminal connector
- Manufactured in accordance to: BS EN 60598-2-22
- 3W LED
- IP Rating: IP20
- Colour temperature: 6000k
- Colour rendering index: >80
- Rated Life: 30,000 hours
- Operating temperature: 0°C to 50°C
- Supplied with ISO pictogram legend as standard: Arrow Up
- Legend maximum viewing distance: 24m
- Battery: LiFePO4 3.2V 1500mAh
- Options available:
  - ISO directional pictogram PVC legends: Arrow Up, Arrow Down, Arrow Left / Right









Part No.	Description	Wattage	Measurement W x H x D	Viewing Distance	IP Rating	Colour Temperature
LXEHS	Emergency Hanging Sign Surface LED	ЗW	300x200x45mm	24m	IP20	6000K
Accessories						
LXEHS/L/AU	Legend Arrow Up	-	300x155x0.5mm	24m	PVC ISO pictogram - Direction Up (2pcs)	
LXEHS/L/AD	Legend Arrow Down	-	300x155x0.5mm	24m	PVC ISO pictogram - Direction Down (2pcs)	
LXEHS/L/ALR	Legend Arrow Left/Right	-	300x155x0.5mm	24m	PVC ISO pictogram - Direction Left/Right (2pcs)	



