

## **Emergency Hanging Sign** Recessed Suspended 3W LED

Recessed mounted, slim profile hanging exit sign, ideal for all commercial, leisure and hospitality emergency lighting applications. Open areas, escape routes and exits.

- 3 hour emergency maintained or non-maintained operation
- Polycarbonate and aluminium housing with interchangeable PVC legends
- Double sided acrylic hanging legend panel: Max. 700mm suspension
- Test function button and LED indicator
- Push-fit terminal connector
- Manufactured in accordance to: BS EN 60598-2-22
- 3W LED
- IP Rating: IP20
- Colour temperature: 6000k
- Colour rendering index: >80
- Rated Life: 30,000 hours
- Operating temperature: -5°C to 40°C
- Supplied with ISO pictogram legend as standard: Arrow Up
- Legend maximum viewing distance: 24m
- Battery: Ni-Cd 3.6V 900mAh
- Options available:
  - ISO directional pictogram PVC legends: Arrow Up, Arrow Down, Arrow Left / Right

















Part No.	Description	Wattage	Measurement W x H x D	Viewing Distance	IP Rating	Colour Temperature
LXEHS/RS	Emergency Hanging Sign Rec/Susp LED	3W	300x200x65mm	24m	IP20	6000K
Accessories						
LXEHS/L/AU	Legend Arrow Up	-	300x155x0.5mm	24m	PVC ISO pictogram - Direction Up (2pcs)	
LXEHS/L/AD	Legend Arrow Down	-	300x155x0.5mm	24m	PVC ISO pictogram - Direction Down (2pcs)	
LXEHS/L/ALR	Legend Arrow Left/Right	-	300x155x0.5mm	24m	PVC ISO pictogram - Direction Left/Right (2pcs)	



