

Emergency Hanging Sign

Recessed 3W LED LiFePO4

Flush recessed mounted, slim profile hanging exit sign, Ideal for all commercial, Leisure and Hospitality emergency lighting applications. Open areas, escape routes and exits.

- 3 hour emergency maintained or non-maintained operation
- Polycarbonate and aluminium housing with interchangeable PVC legends
- Double sided acrylic legend panel
- Test function button and LED indicator
- Push-fit terminal connector
- Manufactured in accordance to: BS EN 60598-2-22
- 3W LED
- IP Rating: IP20
- Colour temperature: 6000k
- Colour rendering index: >80
- Rated Life: 30,000 hours
- Operating temperature: 0°C to 50°C
- Supplied with ISO pictogram legend as standard: Arrow Up
- Legend maximum viewing distance: 24m
- Battery: LiFePO4 3.2V 1500mAh
- Options available:
 - ISO directional pictogram PVC legends: Arrow Up, Arrow Down, Arrow Left / Right



5 YEAR WARRANTY
LED
IP20
EM3 EMERGENCY 3 Hour Duration

| Part No. | Description | Wattage | Measurement W x H x D | Viewing Distance | IP Rating | Colour Temperature |
|--------------------|-------------------------------------|---------|-----------------------|------------------|---|--------------------|
| LXEHS/R | Emergency Hanging Sign Recessed LED | 3W | 300x168x76mm | 24m | IP20 | 6000K |
| Accessories | | | | | | |
| LXEHS/L/AU | Legend Arrow Up | - | 300x155x0.5mm | 24m | PVC ISO pictogram - Direction Up (2pcs) | |
| LXEHS/L/AD | Legend Arrow Down | - | 300x155x0.5mm | 24m | PVC ISO pictogram - Direction Down (2pcs) | |
| LXEHS/L/ALR | Legend Arrow Left/Right | - | 300x155x0.5mm | 24m | PVC ISO pictogram - Direction Left/Right (2pcs) | |