

Emergency Recessed Remote Downlight/CL 3W LED LIFEPO4

High performance emergency downlight for areas where aesthetics are of prime importance. Ideal for all commercial, retail, hospitality and leisure applications

 Escape route and corridor optic design provides uniform illumination with an asymmetrical beam distribution

- 3 hour Non-maintained emergency operation
- Compact aluminium housing construction
- Downlight head, driver and battery pre-wired for easy installation
- Dual LED glows green in standby mode and converts to high power white LED in the event of a mains failure
- 35mm diameter hole cut out size
- Manufactured in accordance to: BS EN 60598-2-22
- 3W LED, 120 Lumen
- IP Rating: IP20
- Colour temperature: 6000k
- Colour rendering index: >80
- Rated Life: 30,000 hours
- Operating temperature: 0°C to 50°C
- Supplied with White bezel
- Battery: LiFePO4 3.2V 1500mAh
- Options available:
 - Open area symmetrical beam version: LXERS













Part No.	Description	Wattage	Measurement W x H	Cut Out Diameter	Lumen Output	IP Rating	Colour Temperature
LXERS/CL	Emergency Recessed Downlight LED with Corridor Lens	3W	42x22mm	35mm	120Lm	IP20	6000K





Web luxna-lighting.com