

LED NCF IP65

- LED Non-Corrosive luminaire, highly efficient, energy saving and maintenance free
- Designed to directly replace traditional twin and single body T8 & T5 fluorescent luminaires
- Luminaire efficacy up to 120 Lumen/Watt
- Impact resistant polycarbonate body and frosted polycarbonate diffuser
- Anti-tamper grade 316 stainless steel clips and locking screws supplied as standard
- Emergency 3 hour-maintained versions with self-test button function fitted as standard
- Surface and suspension mount brackets included
- Fast push-fit, loop in-out terminal block
- Flicker Free LED driver, Non-Dimmable
- IP/IK Rating: IP65/IK08
- Correlated colour temperature: 5000k
- Colour rendering index: Ra80
- Rated life (L70, Ta25°): 50,000 hours
- Operating temperature: -20°C to 45°C (Standard), 0°C to 45°C (*Emergency)
- Voltage and Frequency rating: 220-240V AC ~ 50/60 Hz
- Options available: Side mount PIR or Microwave Sensors



5 YEAR
WARRANTY

LED

IP65

EM3 EMERGENCY MAINTAINED 3 HOURS

Part No.	Description	Wattage	Measurement L x W x H	Lumen Output	IP Rating	*Operating Temperature	Colour Temperature
Standard							
LXNCF12LEDCW	LED 2ft Single	12W	632 x 85 x 81mm	1440 Lm	IP65	-20°C ~ +45°C	5000K
LXNCF22LEDCW	LED 2ft Twin	20W	632 x 103 x 81mm	2400 Lm	IP65	-20°C ~ +45°C	5000K
LXNCF14LEDCW	LED 4ft Single	20W	1232 x 85 x 81mm	2400 Lm	IP65	-20°C ~ +45°C	5000K
LXNCF24LEDCW	LED 4ft Twin	40W	1232 x 103 x 81mm	4800 Lm	IP65	-20°C ~ +45°C	5000K
LXNCF15LEDCW	LED 5ft Single	30W	1532 x 85 x 81mm	3600 Lm	IP65	-20°C ~ +45°C	5000K
LXNCF25LEDCW	LED 5ft Twin	60W	1532 x 103 x 81mm	7200 Lm	IP65	-20°C ~ +45°C	5000K
LXNCF16LEDCW	LED 6ft Single	40W	1800 x 85 x 81mm	4800 Lm	IP65	-20°C ~ +45°C	5000K
LXNCF26LEDCW	LED 6ft Twin	80W	1800 x 103 x 81mm	9600 Lm	IP65	-20°C ~ +45°C	5000K
Emergency							
LXNCF22LEDCW/EM3	LED 2ft Twin EM3	20W	632 x 103 x 81mm	2400 Lm	IP65	0°C ~ +45°C	5000K
LXNCF14LEDCW/EM3	LED 4ft Single EM3	20W	1232 x 85 x 81mm	2400 Lm	IP65	0°C ~ +45°C	5000K
LXNCF24LEDCW/EM3	LED 4ft Twin EM3	40W	1232 x 103 x 81mm	4800 Lm	IP65	0°C ~ +45°C	5000K
LXNCF15LEDCW/EM3	LED 5ft Single EM3	30W	1532 x 85 x 81mm	3600 Lm	IP65	0°C ~ +45°C	5000K
LXNCF25LEDCW/EM3	LED 5ft Twin EM3	60W	1532 x 103 x 81mm	7200 Lm	IP65	0°C ~ +45°C	5000K
LXNCF16LEDCW/EM3	LED 6ft Single EM3	40W	1800 x 85 x 81mm	4800 Lm	IP65	0°C ~ +45°C	5000K
LXNCF26LEDCW/EM3	LED 6ft Twin EM3	80W	1800 x 103 x 81mm	9600 Lm	IP65	0°C ~ +45°C	5000K
Spares							
LXNCF/SS2	Stainless Steel Diffuser Fixing Clip (2x Clips per Pack)						
LXNCF/MK	Mounting Accessory Pack, Suitable for Mounting 1x NCF Fitting						



Email sales@luxna.co.uk



Web luxna-lighting.com