



Main

Range	Acti9
Product name	Acti9 Isobar P A
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Door type	Overall
Provided equipment	Earth stud Enclosure Door Front cover Pan assembly Neutral terminal block Earth terminal block Blanking plate
Colour	Cream (RAL 9001)

Complementary

Enclosure mounting	Surface
Poles description	1P + N
[Ie] rated operational current	125 A at 230/240 V AC
Breaking capacity	25 kA
Overvoltage category	IV
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Incomer device options	Switch disconnecter - 2P Terminal block - 2P RCCB - 2P
Protection device options at outgoing	Miniature circuit breaker (MCB) 63 A Residual current circuit breaker with overcurrent protection (RCBO) 45 A 100 mA Residual current circuit breaker with overcurrent protection (RCBO PoN) 45 A 100 mA
Number of ways	18 ways (1P) outgoing
Enclosure material	Steel
Surface treatment	Epoxy
Surface finish	Powder paint
Height	300 mm
Width	489 mm
Depth	117 mm
Net weight	5.7 kg

Environment

IP degree of protection	IP20 internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529
IK degree of protection	IK05
Pollution degree	3
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.000 cm
Package 1 Width	31.000 cm
Package 1 Length	50.000 cm
Package 1 Weight	6.666 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	42
Package 2 Height	112.000 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	299.972 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes