

DATA SHEET

ODESSA

Odessa V2 30W LED Floodlight Black 840

IP65 LED Slim Floodlights

Supplied with Prewired Flex


Quick and Easy to Install



GENERAL INFORMATION	
Product Code	NOD/V2/30/BK/840
Product Range	Odessa
Product Category	Floodlighting
Fixing Method	Surface
IP Rating	65
IK Rating	N/A
Warranty	5 Years 20000 Hours
DIMENSION/WEIGHT	
Dimensions (L x W x H) (mm)	L=undefined, W=46, H=178
Cut-out Size (mm)	N/A
Product Weight (Kg)	1.31
CONSTRUCTION	
Body Material	Die Cast Aluminium
Body Colour	Black
Optical Material	Glass
Optical Finish	Clear
Termination	1m H05RN-F Flex
Driver - Integral or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A



SIZE	A	B	C	D	E	F
10W	130	125	42	33	52	28
20W	150	150	42	33	52	28
30W	180	178	46	35	62	34
50W	250	235	63	35	117	38



LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	3000
Power Consumption (W)	30
Efficacy (lm/c.W)	102
Operating Temp. (Min/Max)	-20°C - 25 °C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L70:B10 50000
SDCM	<5
ELECTRICAL INPUT	
Voltage (V)	220-240V AC
Operating Frequency	50
In Rush	10A
Drivers per MCB*	N/A
Class	Class 1
Power Factor	>0.95
Cable Entry	Prewired
ELECTRICAL OUTPUT	
Forward Current (mA)	N/A
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	yes
Certificate of Conformity	yes
Accreditations	N/A
BARCODE	
EAN Number	5055943056619

* GUIDE ONLY