



Arcus Compact

Arcus Compact 150W Compact LED low bay with diffuser, 6500K

Low bay LED luminaires offer energy savings and high performance, replacing conventional lighting in general industrial areas, manufacturing, warehousing, leisure facilities and retail environments. The 150W LED low bay has the option to install a microwave sensor behind the frosted diffuser allowing further control and energy savings.

KLBC150D1-W65 ()

Specification

Voltage	220-240Vac 50-60Hz
Voltage (eg 220-240 Vac 50/60Hz)	220-240Vac 50/60Hz
Current (mA)	672
Rated Power (W)	150
CCT Words	Day Light
CCT (K)	6500
Beam Angle(°)	120
Nominal Lifetime (h)	40000
Total Luminous Flux (lm)	15000
Power Factor	0.97
Dimensions L x W x D (mm)	600 x 327 x 84
Weight (kg)	6.23
Protection Rating	Class I
Length (mm)	600
IP Rating	IP20
Ambient Temperature Range (°C)	-20 to 40
Lamp Cap	N/A

Light Source Specification

Dimmable (Y/N/Specific dimmer)	N
CCT	6500K
CRI	83

Optional Gears and Accessories

Accessories 1	Microwave Sensor Module KBTNLS1-MWS2
---------------	--------------------------------------

Technical Drawings

