

# UNIBAT EMERGENCY PACK

UNIBAT-LIFEPO4/EW

**QVIS**<sup>®</sup>

LIGHTING & SECURITY



**2YR\***  
WARRANTY

EMERGENCY RANGE

Specification	UNIBAT
Rated Supply Voltage	220-240VAC
Mains Frequency	50/60 Hz
Mains Input Current, min	17mA
Mains Input Current, max	28mA
Input Power in Mains Operation, min	1.5W ±10%
Input Power in Mains Operation, max	3.5W ±10%
Battery Charge Time	24h
Ambient Temperature	0 to 45 °C
Max. Casing Temperature	60 °C
Mains Voltage Changeover Threshold	According to EN 61347-1, 61347-2-7, 61347-2-13, 62034
IP Rating	IP20
Battery Discharge Current, min (#1 Dial Switch set at EM 5W / EM2.5W)	750 mA / 360 mA
Battery Discharge Current, max (#1 Dial Switch set at EM 5W / EM2.5W)	820 mA / 410 mA
Output Voltage, min	10 Vdc
Output Voltage, max	90 Vdc
Output Constant Current, min (#1 Dial Switch set at EM 5W / EM2.5W)	40 mA / 22 mA
Output Constant Current, max (#1 Dial Switch set at EM 5W / EM2.5W)	330 mA / 195 mA
Emergency Power, min (#1 Dial Switch set at EM 5W / EM2.5W)	4.8W / 2.4W
Emergency Power, max (#1 Dial Switch set at EM 5W / EM2.5W)	5.2W / 2.6W

\* Warranty terms and conditions apply