

FS1326-T BATTERY POWERED CARBON MONOXIDE ALARM


Sensor type	Advanced electrochemical
Battery type	10 year sealed for life lithium



- **Smart RF Ready** - Fit a Smart RF Radio Module (FS1521W2) to wirelessly interlink up to 50 FireAngel Smart RF products, including FireAngel Connect Gateway
- Connects directly to the **FireAngel Connect Gateway**, providing enhanced diagnostic capabilities and realtime notifications to mobile devices (Requires FS1521W2 Smart RF Module)
- Advanced electrochemical sensor calibrated and tested in CO gas
- Easily accessible central button - Test / Smart Silence / Locate
- Integrated flip down bracket
- Single pin or 2 screw fitting options
- Optional tamper resistant feature to prevent unauthorised removal
- Sleep Easy - a low battery chirp can be silenced for 8 hours by pressing the test button, this can be used up to 10 times
- Can be wall-mounted or freestanding offering greater flexibility in positioning
- For additional protection, CO alarms may be placed in rooms individuals spend considerable time whilst awake e.g. bedrooms, living rooms

Technical Specification

Product Dimensions	113.9mm (width) x 93mm (height) x 37.7mm (depth)
Supply voltage	3V DC sealed lithium battery
Technology	Advanced electrochemical and Smart RF Ready
Installation positions	Wall / Freestanding
For use in:	Any room with a fuel burning appliance e.g. boiler, open fires, gas hob or a flue
Operating temperature	-10°C to +40°C
Operating humidity	30% to 90% RH non-condensing
Storage temperature	-20°C to +60°C
Storage humidity	30% to 90% RH non-condensing
Plastic material	UL94 V0 Flame Retardant
Warranty	5 years
Master pack quantity	10
Approvals	EN 50291-1:2018 & EN 50291-2:2010
Weight	86g
Maximum number of connected units	50 Smart RF devices



Create a Safety Network
Add a Smart RF Radio Module to wirelessly interlink up to 50 Smart RF devices with a simple 2 step process.



Smoke Alarm



Heat Alarm



Wireless Alarm Control Unit



Assisted Living Solutions

For further information or sales enquiries, contact your local Specification Manager:
www.fireangel.co.uk