## FICHA TECNICA – DATA SHEET SpeedPRO IP44

## CLAVIJAS AEREAS / MOBILE PLUGS

## Part code CAV1MY

Standards	BS4343	IEC309 IP44 Rated Units
Voltage	240V	17th Edition caravn hook up unit 1 x IP65 Enclosure 1 x Mains Switch 1 x RCBO 16a 30ma Dp 1 x IP44 16A 2P+E Outlet blue 240v 1 x KWH meter 45A
Amps	16a	
IP Rating	44	
Pin	2P+E	
Voltage Range	240v	
Туре	17th Edition Caravan Hook Up	
H Location	6H	



DP B Type 30mA CPRO-32/2B

A single phase 45 Amp 1 module DIN rail mounted meter. Featuring a 5+2 LCD display and MID approval. This meter comes with a pulse output as standard.



Dimensiones y conexiones / Dimensions & connections				
	Dimensiones / Dimensions			
	Altura / Height 320			
	Ancho / Width 205			
	Profundidad / Deep 150			
150 <u>48</u> <u>−</u> 205 <u>−</u> 157 <u>−</u> 138 <u>−</u> 138 <u>−</u> 447	No enlazable / No linkable Norma / Norm: <b>EN62208</b>			
	<ul> <li>With screw terminals</li> <li>Housing material: PA6/ABS</li> <li>Contacts: Nickel-plated contacts</li> <li>IP44 Splashproof</li> </ul>			

Certificaciones / Certifications

Normativa aplicada / Applied Standards

IEC/CEI/EN 60309-1, IEC/CEI/EN 60309-2