

DATA SHEET

EMERGENCY CONVERSION PACKS

M3 Pack V2 LiFePO4 For Recessed Product Ranges

Plug And Play Option For A Range Of Fittings
Comes Complete With Loop in / Loop Out Connectors
Lithium Iron Phosphate Battery LiFePO4



GENERAL INFORMATION		LUMINAIRE PERFORMANCE	
Product Code	N/REC/M3/PACK/V2	Energy Rating	N/A
Product Range	Emergency Conversion Packs	Luminaire Lumens (lm)	N/A
Product Category	Emergency	Power Consumption (W)	N/A
Fixing Method	Recessed	Efficacy (lm/c.W)	0
IP Rating	N/A	Operating Temp. (Min/Max)	0°C - 25 °C
IK Rating	N/A	LIGHT SOURCE	
Warranty	5 Years 20000 Hours	Type	LED
DIMENSION/WEIGHT		Correlated Colour Temp.	N/A
Dimensions (L x W x D) (mm)	L=undefined, W=61, D=30	Colour Rendering Index (CRI)	N/A
Cut-out Size (mm)	N/A	Lumen Depreciation	N/A
Product Weight (Kg)	0.41	SDCM	N/A
CONSTRUCTION		ELECTRICAL INPUT	
Body Material	PC	Voltage (V)	220-240V AC
Body Colour	White	Operating Frequency	50
Optical Material	N/A	In Rush	N/A
Optical Finish	N/A	Drivers per MCB*	N/A
Termination	4x2x2.5mm sq. Push In Terminal	Class	Class 2
Driver - Integral or Remote	Remote	Power Factor	N/A
PACKAGING		Cable Entry	Prewired
Carton Dimensions (mm)	N/A	ELECTRICAL OUTPUT	
Quantity per Outer Carton	N/A	Forward Current (mA)	35 to 100
Total Weight incl. Carton (Kg)	N/A	Forward Voltage (Vf)	20 to 55
		EMERGENCY DATA	
		Mode of Operation	Non-Maintained
		Battery Duration	3 hours
		Battery Type	LiFePO4
		Battery Specification	6.4V 1.5Ah
		Ballast Lumen Factor (BLF)	N/A
		DIMMING	
		DALI	N/A
		OTHER	N/A
		Switch Dim	N/A
		Corridor Function	N/A
		SENSORS	
		Microwave	N/A
		PIR	N/A
		STANDARDS/APPROVALS	
		CE Marked	yes
		Certificate of Conformity	yes
		Accreditations	N/A
		BARCODE	
		EAN Number	5055943074118

* GUIDE ONLY