

Accessible Toilet Reset Point c/w Sounder

Part No. **NC809DBBT**



Overview

A remote reset point c/w sounder specifically designed for use in Accessible Toilet Alarm systems.

Allows calls generated by an NC807C ceiling pull unit to be cancelled at source, i.e. inside the WC.

On-board reassurance LED and sounder provide audible and visual indication of an acknowledged call to reassure users that help is on the way (calls are acknowledged/accepted at an NC943B Single Zone Call Controller or an NC910/20 Range 10 to 20 Zone Call Controller).

Mounts on a standard UK 25mm single gang flush or surface back box.

Also available as part of the NC951 Accessible Toilet Alarm kit.

Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Red Reassurance LED and Sounder.
Controls	Reset button.
Connections	SIG (Signal); -Ve (Negative); +Ve (Positive).
Product dimensions (mm)	87 W x 87 H x 24 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	55g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.
Notes	Connect to an NC943B Call Controller or an NC910 or NC920 10-20 Zone Call Controller to utilise the 800 Series Call System's 'Call Accept' functionality.