Xnightsbridge

DATASHEET




CPL12CT

230V 12W CCT Adj Circular LED Panel- 165mm

www.mlaccessories.co.uk





MLA PART CODE	CPL12CT
DESCRIPTION	230V 12W CCT Adj Circular LED Panel- 165mm
NET WEIGHT (KG)	0.24
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 165 Projection - 15 Base Diameter - 119 Minimum Void - 50
CUT-OUT (MM)	Min./Max. Cut-out - 55 - 125
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
WATTAGE (W)	12
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	850/940/920
LUMENS LIGHT SOURCE ONLY (LM)	1545
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	131.0
CIRCUIT WATTAGE (W)	11.8
ССТ	3000/4000/6000K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.058
DISPLACEMENT FACTOR	>0.9
SVM	0.154
PST-LM	0.231
BEAM ANGLE (DEGREES)	120





Xnightsbridge

LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	No
IC RATED	Yes
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832984030

Date Created: 22/04/2022 14:13





