


DATASHEET



TRLED151

110V IP65 5ft 29W SINGLE LED Non-Corrosive - 4000K

www.mlaccessories.co.uk



MLA PART CODE	TRLED151
DESCRIPTION	110V IP65 5ft 29W SINGLE LED Non-Corrosive - 4000K
NET WEIGHT (KG)	2
FINISH	Yellow
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1563 Height - 90 Width - 94
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	29
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3400
LUMENS LIGHT SOURCE ONLY (LM)	4020
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	142.19
CIRCUIT WATTAGE (W)	28.3
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.260
DISPLACEMENT FACTOR	>0.9
SVM	0.792
PST-LM	0.069
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000

DIMMABLE	No
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	110/230V
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 30W EFFICIENCY FULL LOAD - 90.33% ISOLATION - SELV
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832991533

Date Created: 04/04/2022 15:27

