


DATASHEET



TRLED221

110V IP65 2ft 28W TWIN LED Non-Corrosive - 4000K

www.mlaccessories.co.uk



| MLA PART CODE | TRLED221 |
|-------------------------------|--|
| DESCRIPTION | 110V IP65 2ft 28W TWIN LED Non-Corrosive - 4000K |
| NET WEIGHT (KG) | 1.22 |
| FINISH | Yellow |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 653 Height - 90 Width - 129 |
| CONSTRUCTION | Construction - Polycarbonate |
| CLASS | I |
| IP RATING | IP65 |
| WATTAGE (W) | 28 |
| LAMP TECHNOLOGY | LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 3000 |
| LUMENS LIGHT SOURCE ONLY (LM) | 3630 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 125.98 |
| CIRCUIT WATTAGE (W) | 28.85 |
| CCT | 4000K |
| LIGHT COLOUR | Cool White |
| CRI | >85 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.265 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.752 |
| PST-LM | 0.03 |
| BEAM ANGLE (DEGREES) | 120 |
| LIFE SPAN (HRS) | 25,000 |
| L70B50 LIFESPAN (HRS) | 50,000 |

| | |
|---|--|
| DIMMABLE | No |
| OPERATING TEMPERATURE | -20~35°C |
| INPUT VOLTAGE | 110/230V |
| CABLE ENTRY (MM) | 20 |
| CABLE GLAND INCLUDED | Compression gland |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 21W EFFICIENCY FULL LOAD - 90.11% ISOLATION - SELV |
| WARRANTY | 5year(s) |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5055832991489 |

Date Created: 04/04/2022 15:29

