

# DS3HDN

## 3 Wire Connection IP65 Time Delay Switch

### Features & Benefits

- IP65 weatherproof rating
- Light ON times selectable from 2 minutes to 3 hours via 3 position DIL switch
- Blue LED flashes 1 minute before end time as prompt to user
- 3 wire connection – neutral required



### Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount (3 Wire)
Earth Class Rating	Class I
Operating Temperature	-10°C to +40°C
Ingress Protection Rating	IP65
Connection	3-Wire
Push Buttons	Push To Make
Switch type	Single Pole
Standby Consumption	<0.8W
Number of Channels	1

# Data sheet

## DS3HDN

Light / Automatic Light Switches

<b>Switch rating</b>	16A Resistive 4A Inductive, Low Voltage 20-200W, 150W LED
<b>Time Delay Range</b>	2, 5, 10, 30, 60, 90, 120, 180 Minutes, User Adjustable (DIP Switch)
<b>Permanent ON Facility</b>	No
<b>Multiple Unit Support</b>	No
<b>Cable Entry(s)</b>	x8 M20 Knock Outs Holes Via Back Box

### General

<b>Weight (g)</b>	213
<b>Height (mm)</b>	94
<b>Width (mm)</b>	94
<b>Depth (mm)</b>	57
<b>Body Construction</b>	Polycarbonate
<b>Product Colour</b>	Grey
<b>EAN Number</b>	5012483011812
<b>Guarantee Period</b>	3 Years

# Data sheet

## DS3HDN

Light / Automatic Light Switches

### Line Diagrams

