

DSSN

2 Wire Slave Switch

Features & Benefits

- Slave Unit For DS1N
- Up to 10 Units Can Be Wired With DS1N (Master Unit)



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Wall Box / Surface Mount Patress Box
Earth Class Rating	Class II
Operating Temperature	-10°C to +40°C
Ingress Protection Rating	IP20
Connection	2-Wire
Back Box Minimum Depth (mm)	25
Push Buttons	Push To Make
Standby Consumption	<2VA
Time Delay Range	Mirrors DS1N Settings (Master Switch)
Permanent ON Facility	No

Data sheet

DSSN

Light / Automatic Light Switches

Multiple Unit Support	Up to 10 DSSN slave units (max) can be connected with one DS1N master unit
Cable Entry(s)	Back Entry

General

Weight (g)	77
Height (mm)	84
Width (mm)	84
Depth (mm)	38
Protruding Depth (mm)	20
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Screws
Accessories (Optional)	ZV900 Automatic Switch Load Controller. (Sold separately)
EAN Number	5012483014875
Guarantee Period	3 Years

Line Diagrams

