

FBT4N

4 Hour Electronic Boost Timer and Fused Spur

Features & Benefits

- Ideal for immersion heaters, room heaters, towel rails and lighting
- Replaces existing single gang connection unit or fixed appliance outlets
- Easy push button selection with clear LED output status
- Provides timed output protected by a BS1362 fuse switch



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Wall Box / Surface Mount Patress Box
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Digital
Back Box Minimum Depth (mm)	25
Program Modes	Countdown
Switch type	Single Pole
Standby Consumption	<0.7W

Data sheet

FBT4N

Time / Immersion & General Purpose Timeswitches

Number of Channels	1
Switch rating	13A Resistive, 1000W Incandescent/Halogen, 500W Fluorescent, 200W LED, 100W CFL
Shortest Switching Time	15 Minutes
Time Delay Range	¼ hour, ½ Hour, 1 Hour, 2 Hour or 4 Hour
Permanent ON Facility	No
Cable Entry(s)	Bottom Entry, Back Entry

General

Weight (g)	164
Height (mm)	85
Width (mm)	85
Depth (mm)	42
Protruding Depth (mm)	32
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings
EAN Number	5012483015179
Guarantee Period	3 Years

Data sheet

FBT4N

Time / Immersion & General Purpose Timeswitches

Line Diagrams

