Data sheet LED88N

Light / LED Bulkheads

LED88N

6.5W LED Energy Saver Bulkhead Light

Features & Benefits

- Powerful 6.5W LED energy saving bulkhead light
- Ideal for both indoor and outdoor installation
- Colour temperature:3700K to 4200K
- Simple and quick to fit with fast-fix terminal block connection



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	-20°C to +40°C
Ingress Protection Rating	IP55
Wattage	6.5
Beam Angle	90° x 90°
Energy Efficiency	Class G
Energy Usage	6.5KwH/1000H
Lumen output (Im)	500



A **theben** Group Company

Subject to technical changes and misprints

additional information at: https://www.timeguard.com This data was generated on

17/05/2022

Light / LED Bulkheads

Colour Temperature (K)	3700 - 4200
LED Type	SMD (Intergrated)
Mounting Hole Centres (mm)	60
Multiple Unit Support	Yes
Cable Capacity (mm2)	2.5mm2
Cable Entry(s)	Back Entry

General

Weight (g)	300
Height (mm)	205
Width (mm)	108
Depth (mm)	63.5
Body Construction	Polycarbonate
Product Colour	Black
Accessories (Included)	Fittings
EAN Number	5012483015094
Guarantee Period	3 Years



A **theben** Group Company


Subject to technical changes and misprints

additional information at: https://www.timeguard.com

This data was generated on

17/05/2022

Line Diagrams





Subject to technical changes and misprints

additional information at: https://www.timeguard.com

This data was generated on