

Technical Specification

Lifford Floodlight AC 100W 4000K Black



Product Information

Product Group	Exterior Lighting
Description	Lifford Floodlight AC 100W 4000K Black
Product Name	Lifford
Product Type	LED Floodlight
Product Colour	Black
Warranty	3 Years

General Information

IP Rating	IP65
Operating Temperature	-20 - 30 °C
Beam Angle	120 Degree
Body Material	Diecast Aluminium
Diffuser Material	Tempered Glass

Tel: 01507 328031 | Email: sales@lumineux.co.uk | www.lumineux.co.uk B&T Associates Ltd, Manby Business Park, Manby, Louth, Lincolnshire, LN11 8UT, UK Information and specification is subject to change without prior notice. Lumineux terms and conditions apply.





Technical Specification

Mounting Type	Wall Mount Only

LED Information

LED Туре	SMD
Lumen Output +/- 10%	8185lm
Lumens Per Circuit Watt	85Lm/W
LED Lifetime L70	30000 h
сст	4000K
CRI	>80

Electrical Information

Class	Class I
Circuit Wattage	95.9W
Connection Type	Flying Lead
Cable Length	1m H05RN-F 3 core

Driver Information

Input Voltage	220 - 240V AC
Input Current	0.468 A
Operating Frequency	50 - 60Hz
Power Factor	>0.90

Shipping Information

Product Weight

1.95Kg

Tel: 01507 328031 | Email: sales@lumineux.co.uk | www.lumineux.co.uk B&T Associates Ltd, Manby Business Park, Manby, Louth, Lincolnshire, LN11 8UT, UK Information and specification is subject to change without prior notice. Lumineux terms and conditions apply.





Technical Specification

Carton Dimensions	340mm x 360mm x 280mm
Barcode	5055379533098

Certification

Manufactured in Accordance to	BS EN 60598-1
CE Marked	CE & UKCA


Product Dimensions

(C)	53 mm
(A)	280 mm
(B)	318 mm





Technical Specification



Datasheet generated by https://www.onetimepim.com, last updated: Friday, 02 July 2021 01:03:32

Tel: 01507 328031 | Email: sales@lumineux.co.uk | www.lumineux.co.uk B&T Associates Ltd, Manby Business Park, Manby, Louth, Lincolnshire, LN11 8UT, UK Information and specification is subject to change without prior notice. Lumineux terms and conditions apply.

