

SUPERCLIP™


DATA SHEET



DIRECTIONS FOR USE


Our SuperClips are designed specifically for conduit, armoured and grouped cables. They are suitable for all substrates.

Installation could not be simpler.



Drill a 10mm hole

Your pack of clips will carry instructions on the recommended diameter of drill bit required for your chosen clip.



Slide the clip over the cable

When sliding the clip over the cable, ensure that it is seated into the rounded area.



Compress the Clip & insert into the hole

The clips can be easily compressed by hand. Squeeze the clip legs and simply insert it into the hole.

TESTING AND COMPLIANCE

>1000oC melting point

Meets 90 minute fire time in accordance with DIN4102-12

Meets 120 minute fire time in accordance with BSEN50200

Compliant with the requirements of BS 8519:2010

Salt spray tested to 500 hours

Smoke emission tested to London Underground Standard

Supports tensile loads of 44kg*

Life saver - meets recommendations for

Fire Rated Cable Fixings BS7671 18th Edition



*Average achieved in C35 Grade Concrete

T. +44 (0) 141 465 4858

E. info@linianclip.co.uk

Visit our website to find your nearest stockist

WWW.LINIANCLIP.CO.UK

Check out our website to discover the full range of LINIAN Clips, designed for all your needs.

LINIAN SUPERCLIP SIZE CHART

PART NUMBER	PART DESCRIPTION	SUITABLE FOR	OVERALL DIAMETER	CC EQUIVALENT
1LSB1214	12-14mm LINIAN SuperClip (BLACK)	Heavy Round Cable/ Bunched Cables	Max. 14mm	CC6
1LSB1518	15-18mm LINIAN SuperClip (BLACK)	Heavy Round Cable/ Bunched Cables	Max. 18mm	CC7
1LSB1820	18-20mm LINIAN SuperClip (BLACK)	Heavy Round Cable/ Bunched Cables	Max. 20mm	CC8
1LSB2022	20-22mm LINIAN SuperClip (BLACK)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 22mm	CC9
1LSB2325	23-25mm LINIAN SuperClip (BLACK)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 25mm	CC10
1LSW1214	12-14mm LINIAN SuperClip (WHITE)	Heavy Round Cable/ Bunched Cables	Max. 14mm	CC6
1LSW1518	15-18mm LINIAN SuperClip (WHITE)	Heavy Round Cable/ Bunched Cables	Max. 18mm	CC7
1LSW1820	18-20mm LINIAN SuperClip (WHITE)	Heavy Round Cable/ Bunched Cables	Max. 20mm	CC8
1LSW2022	20-22mm LINIAN SuperClip (WHITE)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 22mm	CC9
1LSW2325	23-25mm LINIAN SuperClip (WHITE)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 25mm	CC10
1LSR1214	12-14mm LINIAN SuperClip (RED)	Heavy Round Cable/ Bunched Cables	Max. 14mm	CC6
1LSR1518	15-18mm LINIAN SuperClip (RED)	Heavy Round Cable/ Bunched Cables	Max. 18mm	CC7
1LSR1820	18-20mm LINIAN SuperClip (RED)	Heavy Round Cable/ Bunched Cables	Max. 20mm	CC8
1LSR2022	20-22mm LINIAN SuperClip (RED)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 22mm	CC9
1LSR2325	23-25mm LINIAN SuperClip (RED)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 25mm	CC10

Recommended Spacing: 300mm
Hole Diameter: 10mm* **Hole Depth: 40mm**
 Supports a max tensile load of 44kg

34-38 Payne Street
 Port Dundas Trading Estate
 Glasgow G4 0LF, UK
 Tel: +44 (0)141 465 4858
 Email: info@linianclip.co.uk

* Varies for best fixing according to substrate