

**DATA SHEET**

**TEXAS**



**Texas LED Twin 5Ft Batten 840**

IP20 Surface LED Fitting  
Steel and Polycarbonate Construction  
Easy Access and Installation



GENERAL INFORMATION	
Product Code	NTE2X5/840
Product Range	Texas
Product Category	Surface Mount
Fixing Method	Surface
IP Rating	20
IK Rating	N/A
Warranty	5 Years 20000 Hours
DIMENSION/WEIGHT	
Dimensions (L x W x H) (mm)	L=undefined, W=63, H=74
Cut-out Size (mm)	0
Product Weight (Kg)	1.75
CONSTRUCTION	
Body Material	PC/Steel
Body Colour	White
Optical Material	PC
Optical Finish	Opal
Termination	3x2x2.5mm sq. Push In Terminal
Driver - Integral or Remote	Integral
PACKAGING	
Carton Dimensions (mm)	N/A
Quantity per Outer Carton	N/A
Total Weight incl. Carton (Kg)	N/A

LUMINAIRE PERFORMANCE	
Energy Rating	N/A
Luminaire Lumens (lm)	7620
Power Consumption (W)	65
Efficacy (l.lm/c.W)	119
Operating Temp. (Min/Max)	-20°C - 25 °C
LIGHT SOURCE	
Type	LED
Correlated Colour Temp.	4000
Colour Rendering Index (CRI)	>80
Lumen Depreciation	L70:B10 50000
SDCM	<5
ELECTRICAL INPUT	
Voltage (V)	220-240V AC
Operating Frequency	50
In Rush	<25A
Drivers per MCB*	B10=10 B16=15 C10=15 C16=20
Class	Class 1
Power Factor	>0.95
Cable Entry	Side /Base
ELECTRICAL OUTPUT	
Forward Current (mA)	N/A
Forward Voltage (Vf)	N/A
EMERGENCY DATA	
Mode of Operation	N/A
Battery Duration	N/A
Battery Type	N/A
Battery Specification	N/A
Ballast Lumen Factor (BLF)	N/A
DIMMING	
DALI	N/A
OTHER	N/A
Switch Dim	N/A
Corridor Function	N/A
SENSORS	
Microwave	N/A
PIR	N/A
STANDARDS/APPROVALS	
CE Marked	yes
Certificate of Conformity	yes
Accreditations	N/A
BARCODE	
EAN Number	5055943074705



\* GUIDE ONLY