

DATA SHEET:

UCLCT4/ UCLCT9/ UCLCT13/ UCLCT18

ISSUE: AKJUL19VOL1



MLA part code	UCLCT4	UCLCT9	UCLCT13	UCLCT18
Description	230V LED CCT Adjustable Linkable Striplight complete with 2m power cord and mounting brackets			
Finish	White / Opal			
Nett weight (kg)	0.052	0.15	0.23	0.3
Dimensions (mm)	Length 277 Width 22.8 Projection 36	Length 538 Width 22.8 Projection 36	Length 838 Width 22.8 Projection 36	Length 1138 Width 22.8 Projection 36
Wattage (W)	4	9	13	18
Lumens (lm)	3000K – 350 ± 5% 4000K – 390 ± 5% 6500K – 370 ± 5%	3000K – 685 ± 5% 4000K – 690 ± 5% 6500K – 675 ± 5%	3000K – 1055 ± 5% 4000K – 1055 ± 5% 6500K – 1025 ± 5%	3000K – 1675 ± 5% 4000K – 1915 ± 5% 6500K – 1780 ± 5%
Efficacy (lm/W)	3000K – 88 4000K – 98 6500K – 93	3000K – 76 4000K – 77 6500K – 75	3000K – 81 4000K – 81 6500K – 79	3000K – 93 4000K – 106 6500K – 99
CCT	3000K / 4000K / 6500K			
LED Colour	Warm White / Cool White / Daylight			
CRI	>80	>80	>80	>80
Circuit Wattage (W)	3.91	8.47	12.43	17.34
Running current (A)	0.018	0.072	0.099	0.077
Power factor	>0.9	>0.5	>0.5	>0.9
Life span (Hrs)	30,000			
Input voltage	Mains 230V 50Hz			
Construction	Polycarbonate			
Class	Class II			
IP rating	IP20			
Dimmable	No			
Warranty	2 Years			
Origin of Manufacture	China			
Declaration of Conformity (held on file)	Yes			
Manufactured in accordance with	BS EN 60598			
EAN	5055832999560	5055832999607	5055832999621	5055832999645