



PVC Sleeving

- **Standard:** UL 224
- **Temperature ranges:** -50°C up to -100°C
- **Colours:** Blue, Grey/Yellow, Brown
- **Use:** Use under acid and alkali
Use with strict environmental requirements
- **Appearance:** No cracking
Smooth, no oil or duty in appearance
- **Application:** This specification applies to insulation use in automotive electronics, terminal lugs, small electrical parts, lead wires of toy motors and transformers etc. It is ideal for application in wire harness, automatic equipment, railway, general manufacturing industry where wire and cable are required to have a protection.



Part No.	Description	Internal Diameter (mm)	Wall Thickness (mm)
YESL2BL	2mm Blue - 100mtr Drum	4.00 (±0.15)	0.50 (±0.10)
YESL2BR	2mm Brown - 100mtr Drum	4.00 (±0.15)	0.50 (±0.10)
YESL2GY	2mm Green / Yellow - 100mtr Drum	4.00 (±0.15)	0.50 (±0.10)
YESL3BL	3mm Blue - 100mtr Drum	5.00 (±0.15)	0.50 (±0.10)
YESL3BR	3mm Brown - 100mtr Drum	5.00 (±0.15)	0.50 (±0.10)
YESL3GY	3mm Green / Yellow - 100mtr Drum	5.00 (±0.15)	0.50 (±0.10)
YESL4BL	4mm Blue - 100mtr Drum	6.00 (±0.15)	0.50 (±0.10)
YESL4BR	4mm Brown - 100mtr Drum	6.00 (±0.15)	0.50 (±0.10)
YESL4GY	4mm Green / Yellow - 100mtr Drum	6.00 (±0.15)	0.50 (±0.10)
YESL6BL	6mm Blue - 100mtr Drum	10.00 (±0.15)	0.50 (±0.10)
YESL6BR	6mm Brown - 100mtr Drum	10.00 (±0.15)	0.50 (±0.10)
YESL6GY	6mm Green / Yellow - 100mtr Drum	10.00 (±0.15)	0.50 (±0.10)