



# P-Clips & Saddles

## Copper One Hole P-Clips & Copper Saddles

- Material Properties: Halogen Free, Low Smoke and Fumes/Fire Resistant
- Working Temperature: 200°C Max.
- Material Characteristics:
  - Excellent Resistant to corrosion
  - Improved Resistance to Wear and Abrasion
  - Good Impact Resistance, Flexibility
  - Compatibility with Food products: Food hygienic properties, long service life
- Smoke and Toxic Fume Emissions Certified to BS 6853: 1987: B 5.2
- Fire Propagation Test Class '0' Certified to BS 476: 1989: Part 6
- Surface Spread of Flame Test Class '1' Certified to BS 476: 1997: Part 7
- Fixing Clip/Saddle: Copper TGIC Free Polyester Powder Coating



Part No.	Colour	Size	Cable Diameter		One Hole Clips		Two Way Saddles	
			Bare (mm)	Covered (mm)	Bare Copper	LSF Coated	Bare Copper	LSF Coated
YRCHL28RE	Red	2L 1.5	5.7	7.2	22	28	222	302
YRCHL30RE	Red	3L 1.5	6.4	7.9	24	30	272	342
YRCHL32RE	Red	2L 2.5	6.6	8.1	26	32	272	342
YRCHL34RE	Red	4L 1.5	7.0	8.5	28	34	302	342
YRCHL37RE	Red	4L 2.5	8.1	9.8	32	37	342	422
YRCHL40RE	Red	7L 1.5	8.4	10.1	32	40	342	422
YRCHL43RE	Red	7L 2.5	9.7	11.4	37	43	382	462
YRCHL28WH	White	2L 1.5	5.7	7.2	22	28	222	302
YRCHL30WH	White	3L 1.5	6.4	7.9	24	30	272	342
YRCHL32WH	White	2L 2.5	6.6	8.1	26	32	272	342
YRCHL34WH	White	4L 1.5	7.0	8.5	28	34	302	342
YRCHL37WH	White	4L 2.5	8.1	9.8	32	37	342	422
YRCHL40WH	White	7L 1.5	8.4	10.1	32	40	342	422
YRCHL43WH	White	7L 2.5	9.7	11.4	37	43	382	462
YRCHL28BLK	Black	2L 1.5	5.7	7.2	22	28	222	302
YRCHL30BLK	Black	3L 1.5	6.4	7.9	24	30	272	342
YRCHL32BLK	Black	2L 2.5	6.6	8.1	26	32	272	342
YRCHL34BLK	Black	4L 1.5	7.0	8.5	28	34	302	342
YRCHL37BLK	Black	4L 2.5	8.1	9.8	32	37	342	422
YRCHL40BLK	Black	7L 1.5	8.4	10.1	32	40	342	422
YRCHL43BLK	Black	7L 2.5	9.7	11.4	37	43	382	462
YRSFL302RE	Red	3L 1.0	5.8	7.3	22	28	342	302
YRSFL342RE	Red	2L 2.5	6.6	8.12	26	32	272	342
YRSFL302WH	White	3L 1.0	5.8	7.3	22	28	342	302
YRSFL342WH	White	2L 2.5	6.6	8.12	26	32	272	342