



# EMERGENCY LUMINARIES SPECIFICATION SHEET




**COLLINGWOOD  
LIGHTING**

01604 495 151  
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

## Salvus Emergency Exit Box

47lm, emergency exit box

### FEATURES

<b>IK rating</b>	IK08
<b>IP rating</b>	IP20
<b>Colour flexibility</b>	Fixed
<b>Input</b>	220-240V 50/60Hz
<b>CRI</b>	>80Ra

### INSTALLATION INFORMATION

<b>Install Connector Type</b>	Push-fit Connector
<b>Inrush Current</b>	12A 56µs
<b>Construction Material</b>	Lens PC Housing PC
<b>Weight</b>	0.6Kg
<b>Maximum ambient temperature</b>	45°C
<b>Electric Class (1, 2, 3)</b>	2

### PHOTOMETRICS @ 25°C

Product code	Feature I	Feature II	Feature III	Wattage	Colour	lm
EMBX35M	Maintained & Non-Maintained	View Dist 35m	Manual Test NiCd	3.5W	6500K	47 lm
EMBX35S	Maintained	View Dist 35m	Self Test LiFePO4	3.5W	6500K	47 lm

### ACCESSORIES

<b>EMBXUP</b>	Pictogram Arrow UP.	Sold Separately
<b>EMBXDO</b>	Pictogram Arrow DOWN.	Sold Separately
<b>EMBXRI</b>	Pictogram Arrow RIGHT.	Sold Separately
<b>EMBXLE</b>	Pictogram Arrow LEFT.	Sold Separately

### GUARANTEE / WARRANTY

2 Year Extended Warranty Manual Test, 3 Year Extended Warranty Self Test

### FEATURES & BENEFITS

Terminals allow for both maintained and non-maintained usage, by simply connecting the cables to the push-fit terminals

Manual test (without button) or self test versions available

NiCd, has proven technology which is widely used


Lithium batteries are long-lasting and have a long-life

Housing is rugged and made from Polycarbonate


35m viewing distance allowing it to be assembled in many different room dimensions

Complying with ISO 3864-1, and proud members of the ICEL

390.3mm



195.3mm



30mm