

## Scutch Comb Chisels

### MATERIAL RECOMMENDATIONS

	●	● Very suitable ● Suitable ● Suitable but better alternative
Heavy Duty Concrete	●	● Suitable but better alternative
General Concrete	●	● Very suitable
Hard Bricks	●	● Suitable
Soft Bricks	●	● Very suitable
Lightweight Blocks	●	● Very suitable
Natural Stone	●	● Suitable
Constructional Granite	●	● Suitable
Limestone	●	● Suitable
Mortar	●	● Very suitable



### USAGE INFORMATION

Prior to using chisels, please ensure your machine has the 'chisel only' function as they are designed to be used on this function only.

Before using the chisel, please ensure the chuck shank is thoroughly lubricated

For use in heavy duty concrete, general concrete, hard bricks, soft bricks, lightweight block, natural stone, constructional granite, limestone, mortar.

Minimal force should be applied when being used.

After using the product continuously for 10-15 minutes the chisel must be removed from the chuck and allowed to cool at room temperature.

Lubrication must be re-applied before re-using. Products can fail on the shank due to temperature build up of 200°C.

Misuse of the product will decrease the maximum time usage significantly.

Shank failure due to temperature build up is not warranted.

### TECH TIP

It is necessary to try to keep all Scutch Comb teeth in contact with the material being chiselled to avoid the comb being levered out of the holder

