



Consumer

Metal Clad Single Phase Garage Consumer Unit

Specification

Part No: ERSMCU5/GU

Enclosure Specifications

- CE Certified
- BS EN 62208
- BS EN 61439-3 when fitted with mains switch or RCD
- Operating Voltage: 230V

Specification	
Number of Modules	5
Depth	118mm
Height	243mm
Width	141mm
EClass Code	27_07

RCD Specifications

- RCD sensitivity: 30mA
- AC Current
- Device can be locked safely in the 'ON' or 'OFF' position using a device lock
- Cable Capacity: 25mm²
- Maximum torque setting: 2.5Nm
- 35mm DIN rail Mounting
- CE & SEMKO Certified
- BS EN61008-1 / EN61008-2-1

Specification	
Number of Poles	2 Pole
Mounting Type	DIN Rail
Breaking Capacity	6kA
Current Rating	63A
Rated Voltage	230V
Height	85mm

MCB Specifications

- Device can be locked safely in the 'ON' or 'OFF' position using a device lock
- Cable Capacity: 25mm²
- Maximum torque setting: 2.5Nm
- 35mm DIN rail Mounting
- CE & SEMKO Certified
- BS EN60898-1

Specification	
Number of Poles	1 Pole
Mounting Type	DIN Rail
Breaking Capacity	6kA
Current Rating	6A, 16A, 32A
Curve Type	Type B
Rated Voltage	230V, 400V



YESSS House, Unit B Foxbridge Way, Normanton, WF6 1TN
AER, Zac du Caillou, Rue Jules Verne, 69630, Chaponost, France

eris-eu.com sales@eris-eu.com