




Product Description:

X7[™] Fixed 7W Fire Rated Downlight


Introducing the latest fire rated IP65 downlight to the Aurora portfolio, the X7[™] comes complete with a plastic white bezel (satin nickel and polished chrome available separately) and integrated driver with loop in/loop out terminal block. The X7[™] is an LED integrated fixed IP65 downlight delivering up to 89lm/W with an overall height of only 58mm, making it ideal for shallow ceiling voids.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-X7/30	7	3000	580	83	60	White	Triac Dimmable
AU-X7/40	7	4000	620	89	60	White	Triac Dimmable


Line Drawing



Polar Curve



Colour



White

Product Features:

- Edge-to-edge multifaceted polycarbonate lens for low glare and halogen like appearance
- Wide 60° beam angle delivers increased light distribution
- Integrated driver with improved loop in/out terminal block for quick and easy installation
- Supplied with a White IP65 bezel (Polished Chrome & Satin Nickel bezel finishes sold separately)
- Insulation coverable
- Patented fire rated downlight without intumescent
- Tested in 30, 60 & 90 min solid timber joist fire rated ceilings
- Tested in 30 min i-joist and open web joist fire rated ceilings
- 3 year warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/50HZ
Power Factor	0.9	IP Rating	IP65
Lifetime L70 (hrs)	35000	Overall Diameter (mm)	88
Weight (Kg)	0.205	Height (mm)	58
Base Diameter (mm)	61	Product Type	Downlights, Fire-Rated Downlight
Cutout Diameter (mm)	65-70	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	25°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.