

# Onyx 200W flood

EL200X3F



## PRODUCT DATA

|                        |                    |
|------------------------|--------------------|
| LUMENS (lm)            | 26000lm            |
| WATTAGE (W)            | 200W               |
| COLOUR TEMPERATURE (K) | 5000K              |
| WEIGHT (kg)            | 4.6kg              |
| BEAM ANGLE             | 120°               |
| WINDAGE                | 0.18m <sup>2</sup> |
| CRI                    | >70                |
| REPLACEMENT FOR        | 500W MH/SON        |
| DIMENSIONS (mm)        | 418x368x56mm       |
| PRODUCT TYPE           | Floods             |
| EFFICIENCY (lm/w)      | 130lm/W            |
| RATED LIFETIME (hrs)   | 25,000hrs          |
| IP                     | 65                 |
| IK                     | 07                 |
| HOUSING COLOUR         | Black              |
| WORKING ENVIRONMENT    | -20°C to 40°C      |
| WARRANTY               | 2 years            |


## KEY FEATURES

The high output of the Onyx 200W flood (3rd generation) makes it a perfect replacement for a 500W MH/SON and is ideal as a high powered floodlight. The input voltage range of 110-240Vac allows for use in both commercial, industrial and construction site lighting. Additionally, by using our optional coastal marine upgrade version (LL004), users are able to install the Onyx in coastal marine areas (Code: LL004).


## COMMERCIAL APPLICATIONS

For external use on: Warehouses, factories, sports facilities, retail outlets, car-parks, construction sites, footpaths, parks, loading bays. Not suitable for swimming pool areas or for use as a low bay or high bay - please contact us for information on our products which are suitable.

## POLAR CURVE DIAGRAM



## CONE DIAGRAM



## DIMENSIONS

