



EMERGENCY LUMINARIES SPECIFICATION SHEET




**COLLINGWOOD
LIGHTING**

01604 495 151
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

LEDEP10

Emergency converter, Self-test

FEATURES

IP rating	IP20
Input	220-240V 50-60Hz

INSTALLATION INFORMATION

Install Connector Type	Mains: Push-fit terminals 0.5 - 2.5mm ² DC: Plug & Play connectors
Insulation Coverable	No
Double Insulation	Yes
Cut Out Size	Ø18mm (status LED) Ø7mm (test button)
Inrush Current	10A
Construction Material	Polycarbonate
Weight	390g
Maximum ambient temperature	0 to 50°C
SELV	Yes
Electric Class (1, 2, 3)	2

GUARANTEE / WARRANTY

3 year extended guarantee

FEATURES & BENEFITS

- Self-test device, simplifying the emergency lighting inspections
- Dual colour Green / Red LED status indicator
- A minimum of 3 hours of emergency lighting
- Built-in protection:
 - open circuit
 - over charging
 - over discharging
 - over temperature
- LiFePO₄, provides long operational life
- Supplied with a test button, whereby a battery duration test can be carried out at anytime
- Synchronizes an automatic battery duration test every 6 months
- Compatible with our Solis panels, Thea commercial downlights, H2 Pro, 1901 and H5 downlights, however this does not apply to trimless

WIRING INFORMATION

Cable / Flying Lead	Plug & Play connectors
Type of Wiring Required	Parallel

ACCESSORIES

No accessories required

PRODUCT CODES

Product code	Finish	Description	Wattage	Feature I	Feature II
LEDEP10	White matt	Emergency converter, Self-test.	2.5W	LiFePO ₄ battery	6.4V 1500mAh

200mm



25mm



55mm