




7

YEAR
WARRANTY*

*With registration.
More information at
www.ledlenser.com

PRODUCT DATA SHEET

P5R CORE Rechargeable LED Torch (CS500)



P5R Core

- The Ledlenser P5R CORE rechargeable LED torch delivers powerful focusable illumination, provides exceptional protection against water/dust ingress and yet is small enough to carry comfortably in a pocket
- 7-year with registration warranty - for complete peace of mind
- Four brightness levels - Boost 500lm, Power 350lm, Mid-Power 130lm, Low Power 15lm, plus Position, Blink, SOS, and Strobe
- Patented Advanced Focusing System - clever engineering enables seamless beam focusing for flood (near) or spot (distance) illumination and any level in-between
- Dimming feature - dim the light intensity to provide just the right level of illumination
- Flicker-free light - prevents a strobe effect, for example on fast moving machinery
- Seal-Tight Technology - supreme level of ingress protection. 100% dust tight. Watertight against the effects of temporary immersion in water between 15cm and 1m for up to 30 minutes. Rated IP68. Ideal for working in dusty or wet environments
- Transport Lock mode - prevents accidental battery drain if switch is inadvertently depressed whilst in transit
- Metal housing - aircraft grade aluminium provides strength and durability whilst being corrosive resistant
- Environmentally friendlier - housing and rechargeable battery lasts significantly longer than disposable alternatives
- Low Battery warning - allows user time to replace batteries before power runs out
- Battery status indicator - indicates how much charge is still left in the battery
- Charging indicator - indicates when battery is fully charged during recharging
- Magnetic Charge System - water and dust tight, fuss-free magnetic contact charging. No need to remove battery out of its housing
- Fast charging via supplied magnetic contact charging cable - just 2 hours to full charge
- Supplied with 1 rechargeable battery (L-ion 14500), wrist-strap, magnetic contact charging cable

TECHNICAL DATA

Length defocused [mm]	123
Length focused [mm]	127
Head diameter [mm]	29
Tube diameter [mm]	22
Weight incl. batteries [g]	106
Weight without batteries [g]	85
Focus function	Yes
Head material	Aluminum alloy
Tube material	Aluminum alloy
Optic	Plastic lense (PMMA)
Cartridge	No

POWER SUPPLY

Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion 14500
Battery replaceable	Yes
Total battery voltage [V]	3.7
Total battery capacity [mAh]	750
Total battery energy ² [Wh]	2.77
Rechargeable	Yes
Charging time ⁵ [min]	120
Energy modes	Constant Light
Energy status indicator	Battery Indicator, Charge Indicator, Low Battery Warning

FURTHER SPECIFICATIONS

IP class	IP68
Drop test (drop height) [m]	2
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Boost, Low Power, Mid Power, Power, Position, Blink, S.O.S., Strobe

LIGHT SOURCE

Amount LEDs	1
LED type	High Power LED
Colour	White
Colour temperature [K]	6000 to 7500
Colour rendering index (CRI)	70

LIGHT VALUES

ANSI – Constant Light	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]	500	350	130	15
Beam distance ¹ [m]	250	180	110	40
Run time ¹ [h]		1	3.5	25

SWITCH

Front Switch

FEATURES

Dimmable , Transportation lock , Flicker Free, Memory Function, Back-Up Light

TECHNOLOGIES

Advanced Focus System³, Smart Light Technology, Magnetic Charge System, Emergency Light, Temperature Control System, Seal-Tight Technology

P5R Core

PACKAGING AND LOGISTICS



Exemplary Packaging Illustration

PACKAGING INFORMATION

Type of packaging	Box
Supplied with	1 set of rechargeable batteries, Hand strap, Magnetic charging cable
Item No.	502178
Customs tariff number	85131000
Colour	black
STERLING RRP ex / incl vat (£)	£58.29 / £69.95
EURO RRP ex / incl vat (€)	€56.87 / €69.95

SINGLE PACKAGE

Dimensions W x H x D [cm]	14.5 x 8.5 x 8.5
Gross weight [g]	263
GTIN-13	4058205020428

EXPORT CARTON

Unit	24
Dimensions W x D x H [cm]	39.5 x 30 x 34.5
Gross weight [kg]	6.4
GTIN-13	4058205020442

P5R Core

ACCESSORIES

PRODUCT CATEGORY	ITEM NUMBER	PRODUCT NAME	RRP ex / incl vat
Battery	500985	14500 Li-Ion rechargeable battery 750 mAh	TBC
Color filter / Signal caps	502239	Color Filter Set 29.5mm	TBC
Fastenings / Brackets	502249	Lamp Adapter Type B	TBC
Charger / Cable	502259	Charging Station Type A	TBC
Fastenings / Brackets	7799-PT	Universal Rotating Holder/Mount for Torch Type B	£9.13 / £10.95 €9.72 / €11.95
Charger / Cable	502265	Magnetic Charging Cable Type A	TBC
Charger / Cable	0380	USB Car Charger	£9.16 / £11.00 €9.72 / €11.95
Charger / Cable	502271	USB Adapter 2.4A	TBC

P5R Core

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurement values according to ANSI FL1 in the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting, and to battery duration (hours/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light is equipped with (a) colored LED(s), the measurement values are given for the white light or the white LED. If the light has different energy modes, the measurement is made based on the "energy saving mode".

2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.

3) EP Patent 1880139, US Patent 7,461,960

5) Charging time varies by hardware used.