

# Onyx 150W flood

EL150X3F



## PRODUCT DATA

LUMENS (lm)	19500lm
WATTAGE (W)	150W
COLOUR TEMPERATURE (K)	5000K
WEIGHT (kg)	3.35kg
BEAM ANGLE	120°
WINDAGE	0.14m <sup>2</sup>
CRI	>70
REPLACEMENT FOR	400W MH/SON
DIMENSIONS (mm)	364x315x54mm
PRODUCT TYPE	Floods
EFFICIENCY (lm/w)	130lm/W
RATED LIFETIME (hrs)	25,000hrs
IP	65
IK	07
WORKING ENVIRONMENT	-20°C to 40°C
WARRANTY	2 year


## KEY FEATURES

The high output of the Onyx 150W flood (3rd generation) makes it a perfect replacement for a 400W MH/SON and is ideal as a high powered floodlight. The input voltage range of 110-240Vac allows for use in both commercial, industrial and construction site lighting. Additionally, by using our optional coastal marine upgrade version, users are able to install the Onyx in coastal marine areas (Code: LL003).


## COMMERCIAL APPLICATIONS

For external use on: Warehouses, factories, sports facilities, retail outlets, car-parks, construction sites, footpaths, parks, loading bays. Not suitable for swimming pool areas or for use as a low bay or high bay - please contact us for information on our products which are suitable.

## POLAR CURVE DIAGRAM



## CONE DIAGRAM



## DIMENSIONS

