Xnightsbridge


DATASHEET



SPIKE4BL

230V IP65 4W LED Wall/ Spike Light 3000K

www.mlaccessories.co.uk





MLA PART CODE	SPIKE4BL
DESCRIPTION	230V IP65 4W LED Wall/ Spike Light 3000K
NET WEIGHT (KG)	0.51
FINISH	Black
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 60 Overall Height - 305 Spike Length - 173
CONSTRUCTION	Construction - Die-cast aluminium
CLASS	I
IP RATING	IP65
IK RATING	IK06
WATTAGE (W)	4
LAMP TECHNOLOGY	CoB LED
LAMP INCLUDED	Yes
LUMENS (LM)	355
LUMENS LIGHT SOURCE ONLY (LM)	460
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	136.79
CIRCUIT WATTAGE (W)	4.23
ССТ	3000K
LIGHT COLOUR	Warm White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.036
SVM	0.01
PST-LM	0.03
BEAM ANGLE (DEGREES)	20
LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	15,000





Xnightsbridge

DIMMABLE	No
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	3
CABLE TYPE	3 x 1.0mm² H05RN-F
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 3.5W OUTPUT VOLTAGE - 3-10V OUTPUT CURRENT - 350mA EFFICIENCY FULL LOAD - 80 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270805642

Date Created: 25/04/2022 15:16





