


DATASHEET



WP15CTP

230V IP65 15W CCT Wall Pack Complete with Photocell

www.mlaccessories.co.uk



MLA PART CODE	WP15CTP
DESCRIPTION	230V IP65 15W CCT Wall Pack Complete with Photocell
NET WEIGHT (KG)	1.131
FINISH	Black
DIFFUSER	Prismatic
DIMENSIONS (MM)	Height - 218 Width - 147 Projection - 78
CONSTRUCTION	Construction - Die-cast aluminium
CLASS	I
IP RATING	IP65
WATTAGE (W)	15
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1790/1835/1955
LUMENS LIGHT SOURCE ONLY (LM)	2045
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	139.8
CIRCUIT WATTAGE (W)	14.63
CCT	3000/4000/5000K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.066
DISPLACEMENT FACTOR	>0.9
SVM	0.035
PST-LM	0.05
BEAM ANGLE (DEGREES)	105
LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	50,000

DIMMABLE	No
OPERATING TEMPERATURE	-40~45°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	Blind grommet
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 15W OUTPUT VOLTAGE - 50-70V OUTPUT CURRENT - 230mA POWER FACTOR - 0.9 EFFICIENCY FULL LOAD - 86.6 AMBIENT TEMPERATURE (Ta) - 55°C CASE TEMPERATURE (Tc) - 85°C
SENSOR TYPE	Photocell
SENSOR OVERRIDE	No
SENSOR LUX SETTINGS	On <25lx, Off >130lx
STANDBY POWER	0.41W
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270807295

Date Created: 25/04/2022 09:42

