




01604 495 151
collingwoodlighting.com

-  collingwoodled
-  /collingwoodlighting
-  collingwoodlighting

H2 Pro

Fixed fire-rated, colour and lumen switchable downlight with easy-fit connector

Features

IP rating	IP65
Colour flexibility	CCT Switchable
Tilttable	No
UGR	28
Dimmable	Yes
Input	220-240V 50/60Hz
LED Lifetime	70,000h L70
CRI	>80Ra
SDCM	3SDCM
Flicker Free	Yes
Emergency version available	Yes

Installation information

Install Connector Type	Easy-fit connector
Insulation Coverable	All insulation
Cut Out Size	Ø 64-72mm
Bathroom zone	1
Inrush Current	1A 7.5ms
Construction Material	Mild steel / V0 rated plastic
Maximum ceiling thickness	40 mm
Weight	270g
Maximum ambient temperature	40°C
SELV	Yes
Building regulations	Part B, C, E, P & L
Ceiling Joist Approvals	Solid timber, I-Joist and Metal Web
Electric Class (1, 2, 3)	2

Guarantee

7 year extended warranty

Features & benefits

- Colour switchable between 2700K, 3000K and 4000K
- High efficacy of 130lm/W
- Insulation coverable
- Wattage switchable between 5W and 7W
- Compatible with Collingwood smart system
- Quick and easy installation with easy-fit connector
- Integrated emergency option available
- Compatible with twist and lock bezels
- 2 part, push fit, loop in/ loop out connector
- Fixed position downlight

Photometrics @ 25°C



Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
DLE5245500	Bezel sold separately	5W	2700K	55°	550	110	554
DLE5245500	Bezel sold separately	5W	3000K	55°	650	130	654
DLE5245500	Bezel sold separately	5W	4000K	55°	650	130	654
DLE5245500	Bezel sold separately	7W	2700K	55°	750	107	755
DLE5245500	Bezel sold separately	7W	3000K	55°	850	121	856
DLE5245500	Bezel sold separately	7W	4000K	55°	850	121	856
DLE5245500EM	Bezel sold separately	5W	2700K	55°	550	110	554
DLE5245500EM	Bezel sold separately	5W	3000K	55°	650	130	654
DLE5245500EM	Bezel sold separately	5W	4000K	55°	650	130	654
DLE5245500EM	Bezel sold separately	7W	2700K	55°	750	107	755
DLE5245500EM	Bezel sold separately	7W	3000K	55°	850	121	856
DLE5245500EM	Bezel sold separately	7W	4000K	55°	850	121	856

Wiring information

Cable / Flying Lead	0.15m
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm ²) or 3-core cable (R02V 3x1.5mm ²)
Type of Wiring Required	Parallel



Beam angle: 55°



LED driver

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	N/A	Yes	N/A	N/A	N/A


Accessories


DLCVT110	Downlight Converter Plate	Sold Separately
DLCONVERT70	Downlight Converter Plate	Sold Separately
DM298FP	Faceplate Dimmer	Sold Separately
DM298GRID	Grid Dimmer	Sold Separately
Collingwood Smart System	Range available to turn the ordinary extraordinary	Sold Separately
H2 Bezels	Twist and lock bezels	Sold Separately
LEDEP11	Emergency kit	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

 collingwoodled

 /collingwoodlighting

 collingwoodlighting

H2 Pro

The H2 Pro downlight is one of a kind. The lumen output and the colour temperature can be changed via switches on the driver. This flexibility is valuable and offers peace of mind that you have a downlight that is capable of fulfilling the requirements of the majority of installations. The H2 Pro has a 7 year extended warranty, along with 70,000 hours of LED lifetime, it is a fit and forget solution.