

## Cable Management / Conduit Accessories

### Dome Cover Malleable Galv 25mm



#### Technical Specification

<b>Product Code</b>	25GDCM
<b>Feature 2</b>	Conforms to BS EN 61386-21
<b>Barcode</b>	5012739609978
<b>Cable Hole Ø</b>	25
<b>CE</b>	Y
<b>Colour</b>	Self Colour
<b>Company DUNS Number</b>	216156018
<b>Corrosion Test</b>	Y
<b>Country of Origin</b>	China
<b>Finish body</b>	Galvanised
<b>Fixings supplied with product</b>	N
<b>Galv Plating Thickness</b>	>45µm
<b>Greenbrook Guarantee (Years)</b>	1

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)

Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)

<b>HS Code</b>	7307991090
<b>Installation method</b>	Surface mount
<b>Materials Main Body</b>	Steel
<b>Min Order Qty</b>	20
<b>Minimum Installation Temp</b>	-5
<b>Operating Temperature Range max C</b>	65
<b>Operating Temperature Range min C</b>	-5
<b>Pack Contents</b>	20
<b>Package Product Max. Length (mm)</b>	200
<b>Package Product Max. Height (mm)</b>	70
<b>Package Product Max. Width (mm)</b>	190
<b>Package Product Weight gross (g)</b>	2290
<b>Product (only) Max. Width (mm)</b>	25dia
<b>Product Weight net (g)</b>	113
<b>Sales Pack Qty</b>	20
<b>StatusCode</b>	Active
<b>Thread Diameter</b>	M25
<b>Thread Diameter Ø</b>	M25
<b>UKCA</b>	Y
<b>Working Temperature</b>	-5 to 65 C

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)