

Cable Management / Conduit Accessories

ME Lockring SC 32mm



Technical Specification

Product Code	32SCME
Feature 1	Mild Steel
Feature 2	Conforms to BS EN 61386-21
Barcode	5012739614156
CE	Y
Colour	Self Colour
Company DUNS Number	216156018
Country of Origin	India
Finish body	Matt
Fixings supplied with product	N
Galv Plating Thickness	>8µm
Greenbrook Guarantee (Years)	1
HS Code	7318190090
Installation method	Lock nut
Material Thickness	2.87
Materials Main Body	Steel

Tel No: 01279 772 772

Email: sales@greenbrook.co.uk

Website: www.greenbrook.co.uk

Min Order Qty	100
Minimum Installation Temp	-5
Operating Temperature Range max C	65
Operating Temperature Range min C	-5
Pack Contents	50
Package Product Max. Length (mm)	150
Package Product Max. Height (mm)	60
Package Product Max. Width (mm)	115
Package Product Weight gross (g)	1342
Product (only) Max. Width (mm)	32 dia
Product Weight net (g)	13
Sales Pack Qty	100
Standards	BS EN 61386-21
StatusCode	Active
Thread Diameter	M32
Thread Diameter Ø	M32
UKCA	Y
Working Temperature	-5 to 65 C

Tel No: 01279 772 772

Email: sales@greenbrook.co.ukWebsite: www.greenbrook.co.uk