

Cable Management / Malleable Conduit Boxes

Cond Box Prem Through + Ext Galv 20mm



Technical Specification

Product Code	B20G2E
Feature 1	Galvanised steel
Feature 2	Conforms to BS EN 61386-21
Barcode	5012739609275
Cable Hole Ø	20
CE	Y
Colour	Self Colour
Company DUNS Number	216156018
Corrosion Test	Y
Country of Origin	China
Finish body	Hot dip Galvanised
Fixings supplied with product	N
Galv Plating Thickness	>45µm
Greenbrook Guarantee (Years)	1
HS Code	7307191090
Ingress Protection (IP)	IP30
Installation method	Surface mount
Material Thickness	2

Tel No: 01279 772 772

Email: sales@greenbrook.co.uk

Website: www.greenbrook.co.uk

Materials Main Body	Malleable Iron
Min Order Qty	10
Minimum Installation Temp	-5
Operating Temperature Range max C	65
Operating Temperature Range min C	-5
Pack Contents	10
Package Product Weight gross (g)	1995
Product (only) Max. Height (mm)	25
Product (only) Max. Width (mm)	65 Dia
Product Weight net (g)	198.5
Sales Pack Qty	10
StatusCode	Active
Thread Diameter	M20
Thread Diameter Ø	M20 / M4
UKCA	Y
Working Temperature	-5 to 65 C

Tel No: 01279 772 772

Email: sales@greenbrook.co.ukWebsite: www.greenbrook.co.uk