

## Connectors / Porcelain Connector

### Connector Porcelain 15A 2P CHF



#### Technical Specification

<b>Product Code</b>	PCC152
<b>Feature 1</b>	IP 20
<b>Feature 2</b>	Nickel plated brass terminals
<b>Feature 3</b>	Max temp 350 degrees C
<b>Feature 4</b>	Chemical resistant
<b>Barcode</b>	5012739622700
<b>CE</b>	Y
<b>Colour</b>	White
<b>Company DUNS Number</b>	216156018
<b>Country of Origin</b>	China
<b>Current (I)</b>	15
<b>Finish body</b>	Matt
<b>Frequency (Hz) max</b>	60

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)

Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)

<b>Frequency (Hz) min</b>	50
<b>Greenbrook Guarantee (Years)</b>	1
<b>HS Code</b>	6914100000
<b>Ingress Protection (IP)</b>	IP20
<b>Installation method</b>	Surface mounting
<b>Materials Main Body</b>	Porcelain
<b>Min Order Qty</b>	20
<b>Operating Temperature Range max C</b>	350
<b>Package Product Max. Length (mm)</b>	100
<b>Package Product Max. Height (mm)</b>	20
<b>Package Product Max. Width (mm)</b>	95
<b>Package Product Weight gross (g)</b>	460
<b>Product (only) Max. Depth (mm)</b>	40
<b>Product (only) Max. Height (mm)</b>	15
<b>Product (only) Max. Width (mm)</b>	23
<b>Product Weight net (g)</b>	23
<b>Sales Pack Qty</b>	20
<b>Standards</b>	BS 60998
<b>StatusCode</b>	Active
<b>UKCA</b>	Y
<b>Voltage (VAC) MAX (V)</b>	450
<b>Voltage (VAC) Rated (V)</b>	230
<b>Working Temperature</b>	Max 350 C
<b>Feature 5</b>	Galvanised steel screws

Tel No: 01279 772 772

Email: [sales@greenbrook.co.uk](mailto:sales@greenbrook.co.uk)Website: [www.greenbrook.co.uk](http://www.greenbrook.co.uk)