

SAFETYSURE RCD SOCKETS & FUSED CONNECTION UNITS

**GREEN
BROOK**
ELECTRICAL

- + Mechanical flag trip indicators
- + Mechanically latched - no need to reset after power loss
- + All products have separate 'Test' & 'Reset' buttons
- + Metalclad all supplied with metal back boxes
- + 1 year guarantee



M92W



M92M



M22W



M22M



M22SW



M22SM

	M22W	M22M	M22SW	M22SM	M92W	M92M
Description	RCD Unswitched Socket		RCD Switched Socket		RCD Fused Connection Unit	
Product Finish	White	Metalclad	White	Metalclad	White	Metalclad
Barcode	5012739 608704	5012739 608711	5012739 641510	5012739 641534	5012739 608728	5012739 608735
Voltage	230V AC ~ 50Hz				230V AC ~ 50Hz	
Max Operating Current	13A (3A inductive)				13A (3A inductive)	
Rated Trip Current	30mA				30mA	
Typical Trip Speed	<40mS				<40mS	
RCD Contact Break	Double Pole				Double Pole	
Product Dimensions	H86.5 X W147 x D35mm (16mm surface projection)	H86.5 X W147 x D50mm	H86.5 X W147 x D35mm (16mm surface projection)	H86.5 X W147 x D50mm	H86.5 X W86.5 x D37mm (16mm surface projection)	H87 X W87 x D50mm (Inc back box)
Product Weight	230g	510g	231g	507g	162g	351g
Guarantee	1 Year				1 Year	
Conforms To	BS7288:2016 & BS 1363				BS7288:2016 & BS 1363	

TECHNICAL DATA SHEET

**GREEN
BROOK**
ELECTRICAL

Tel: 01279 772 772

Fax: 01279 422 007

Email: sales@greenbrook.co.uk

www.greenbrook.co.uk

