

SOCKET BOX TIMERS

Mechanical & Electronic Options

- + Ideal for most heating applications
- + Timer 'ON' status indicator
- + Fits 35mm dual appliance socket box, should you require the timer next to a fused spur or socket outlet
- + Will fit directly to any 35mm deep socket box fitted with an earth terminal
- + T108A-C is suitable for discharge lighting applications
- + All products are clam packed for ease of display
- + 1 year guarantee



T100A-C



T101A-C



T105A-C



T108A-C

	T100A-C	T101A-C	T105A-C	T108A-C
Description	24 Hour Mechanical	7 Day Mechanical	7 Day Electronic	7 Day Electronic
Max Load	16A Resistive Load 2A Inductive Load	16A Resistive Load 2A Inductive Load	16A Resistive Load 2A Inductive Load	16A Resistive Load 8A Inductive Load
Product Finish	White			
Barcode	5012739638671	5012739638688	5012739638695	5012739638701
Product Weight	130g	130g	150g	150g
Product Dimensions	H77 x W72 x D43mm (Plate 86 x 86mm)			
Voltage	230V AC			
Battery Back Up	-	-	150 Hours	150 Hours
Display	Mechanical - Analogue Clock Face	Mechanical - Analogue Clock Face & Minute Hand Indicator	Electronic - Digital Display	Electronic - Digital Display
Settings	98 On / Off, On/Timer/Off Switch Selector	84 On / Off, On/Timer/Off Switch Selector	24 On / Off, Summer Time Setting Option	24 On / Off, Summer Time Setting Option & Random Setting Option
Guarantee	1 Year			
Conforms To	BS EN 60730-1, BS EN 60730-2-1, KEMA-KEUR BS Certification mark - BS EN 60730-2-7			