

Product Code: CSP033

Luckinslive 422559786

Description: Smart Temperature & Humidity Sensor



General Information

Materials	Housing: Polycarbonate	Electronics: PCB & Electronic Components
Operating Voltage (DC)	3	
Battery Type	CR 2032 (Supplied)	
Battery Lifetime (Approx.)	1 Year (Dependent On Use)	
Protocol	Zigbee	Signal Transmission Frequency 2.4GHz
Temperature Accuracy (%)	±3	
Indicator Colour	Blue	
Ingress Protection	IP20	
Working Humidity	0%-100%RH (Non-condensing)	
Operational Temperature (°C)	-10 to +50	
Warranty (Years)	3	

Standards BS EN 60950-1, BS EN 55035, BS EN 61000-3-2, BS EN 61000-3-3, BS EN 62311

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Control linked receivers through the ClickSmart+ app
Send activation alerts to your phone

Components Supplied Smart Temperature & Humidity Sensor CR 2032 Battery Reset Key Instruction Manual

Installation Overview Suitable for ceiling or wall mounting.
Self-adhesive pad applied ready for installation.

Programming Information With hub and app setup with sensor having battery installed, using the pin supplied press the reset button for five seconds and the sensor LED will start flashing. Can be paired with hub via app.

