

Product Code: OA20021AG

Luckinslive 408392349

Description: 20AX 1 Gang 2 Way IP66 Weatherproof Switch Unit



General Information

Dimensions (mm)	91 (W) x 106 (H) x 72.5 (D)			
Colour	Anthracite Grey			
Gasket Colour	Black			
Materials	Cover, Housing & Clip:	Polycarbonate	Seal & Gasket:	Rubber
	Switch Membrane:	Neoprene	Switch:	Urea
	Rear Housing:	Nylon	Terminals:	Brass
	Terminal Screws:	Steel & Yellow Passivated	Contacts:	Silver "on-lay" Copper / Brass
	Internal Busbars:	Formed Pressed Brass		
Anti Microbial Certified	No			
Operating Voltage (AC)	250	Frequency (Hz)	50	
Inductive Load Rating (AX)	20			
Load Rating Comments	Suitable for Fluorescent or Inductive Loads			
Termination Type	Screw			
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2	
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 1 x 4			
Modular Rocker Switches	Yes			
2 Way Switch	Yes			
Back Box Knockouts - Total (mm)	5 x Ø20			
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Bottom (mm)	1 x Ø20	
Back Box Knockouts - Rear (mm)	1 x Ø20	Back Box Knockouts - Sides (mm)	1 x Ø20	
Ingress Protection	IP66			
Operational Temperature (°C)	-5 to +40			
Warranty (Years)	20			

Standards BS EN 60669-1, BS EN 60529

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 Interchangeable with 20AX modules in the GridPro Range. **GRIDPRO**

