

Product Code: CL675

Luckinslive 407530788

Description: 13A 1 Gang Double Pole Key Lockable Switched Socket With Neon (Double Plate)



General Information

Dimensions (mm)	140 (W) x 80 (H) x 42 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Metal Clad	
Colour	Grey	
Insert Colour	White	
Materials	Front Plate & Mounting Box:	Insert: Urea
	Electrophoretically Coated Steel	Neon Lens: Polycarbonate
	Earth Plate & Yoke: Mild Steel	Terminal Screws: Steel & Yellow Passivated
	Terminals: Brass	GridPro Module: GM2018PW
	Internal Busbars: Formed Pressed Brass	Frequency (Hz) 50
Operating Voltage (AC)	250	
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4	
Switched	Yes (via Key)	
Modular Rocker Switches	Yes	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Neon Indicator	Yes	Indicator Colour Red
Product Marking	On & Off	
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	7 x Ø20	Back Box Knockouts - Bottom (mm) 2 x Ø20
Back Box Knockouts - Top (mm)	3 x Ø20	Back Box Knockouts - Sides (mm) 1 x Ø20
Back Box Knockouts - Rear (mm)	None	
Back Box Earth Terminal Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS EN 60669-1, BS 1363-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Two keys provided (Spare keys available: SP660)

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

